

CITY OF RANCHO PALOS VERDES DEPARTMENT OF PUBLIC WORKS REVOCABLE ENCROACHMENT PERMIT

30940 Hawthorne Blvd., Rancho Palos Verdes 90275 (310) 544-5252 (Ph) (310) 544-5292 (Fax)

Area	Permit No.

Work Location:

APPLICANT TO	O FILL IN (PLEASE PRINT)			
	│ □ Same as Permittee/Owner			
Permittee/Owner	ContractorAddress	Contractor		
AddressZip Code	_ City	Zip Code		
Telephone	_ Telephone			
E-Mail Address	_ E-Mail Address			
DESCRIPTION OF WORK				
□Special Event □ Trench/Excavation □ Utility Work		e/lateral Sidewalk		
 APPLICANTS MUST ADHERE TO ALL CITY STANI MUST POST NO PARKING SIGNS 72-HOURS PRIO 				
(A HARD COPY OF PERMIT MUST, the undersigned permittee hereby certify and agree to the following That I or the entity on whose behalf this certification is given, hold a cu License.				
Standards Plans, current California MUTCD manual and the City Mur That in consideration of the granting of this permit, the City their officers or employees thereof shall be saved harmless by the a or property, happening or occurring as the proximate result of any of may be granted in response thereto, and that all of said liabilities are interferes with the future use of the Right of Way by the general public expense of the permittee/owner or his successor in interest. MOCK UP DISPLAY AND DUMPSTER PERMITS ARE N	by of Rancho Palos Verdes, City wherein the permit work applicant from any liability or responsibility for any accide the work undertaken under the terms of this application be hereby assumed by the applicant. It is further agreed to, it must be removed or relocated, as designated by the	dent, loss or damage to person and the permit or permits which that if any part of this installation e Director of Public Works at the		
(Non-skid plates required for dumpsters over 6% grade) MOCK UP CONSTRUCTION PERMITS VALID FOR 10	•			
ALL OTHER PERMITS ARE VALID FOR A PERIOD OF 90 C	CALENDAR DAYS AFTER THE APPROVAL DAT	E SHOWN BELOW		
By:				
Permittee/Contractor Signature Date				
	and PERMIT FEES: (Office Use Only)	ф (DM)		
☐ City Business Lic. No	Base Permit Fee	\$(RW)		
☐ Contractor Lic. No(Attach copy of CA State online verification)	Traffic Engineer Plan Check	\$ T4/TD#_		
☐ Certificate of Insurance with Additional Insured Endorse (Copy of Policy Required)	ement Improvement Plan Check Fee	\$ T4/TD#_		
Worker's Compensation Insurance (Copy of Policy Required)	Inspection Fee	\$T4/TD#_		
□ Signed N.P.D.E.S. Compliance Certification	Special Event Fee	\$T4/TD#_		
☐ Signed Hold Harmless	County Sewer Saddle Fee	\$(RW)		
□ NPDES & BMP Guidelines given to Permittee	TOTAL FEE	\$		
-	Itility Invoice No. 101-0000-115-40			
Approved: (Not valid unless approved by Department) Date	Permit Completed:			

- Encroachment Permits may require a minimum of 10 working days of FIRST submittal for Excavation, Haul Routes and/or Traffic Control Plans.
- All Mock ups shall be installed at least two weeks prior to any Public Hearing related to the proposed construction.

Call "DIG ALERT" at 1-800-227-2600 at least 72 hours prior to any construction.

- All work, unless otherwise specified, shall be done in accordance with the current edition of the STANDARD SPECIFICATIONS FOR PUBLIC WORKS CONSTRUCTION.
- Any staging of materials in the City Right-of-Way requires prior approval.
- Haul Routes must be approved 48 Hours prior to entering the City.
- The Permittee/Contractor must follow the latest National Pollutant Discharge Elimination System (NPDES) & Best Management Practices (BMP's) guidelines.
- Before work on any sewer line begins, a permit must be issued by the City of Rancho Palos Verdes Building and Safety Division in addition to this permit. For information on sewer permits call (310) 544-5244 and ask for Building and Safety.
- When permittee tunnels under existing curbs, gutters and sidewalks, the excavated trench shall be back-filled with cement grout as described in the Standard Specifications.
- A.C. Pavement shall be saw-cut beyond edge of trench as specified by APWA Standards.
- Asphalt shall be placed in one-inch lifts or as directed by Department of Public Works Staff.
- When compaction or material tests are required, all costs are to be borne by the permittee.
- A one-sack sand slurry mixture may be required for compaction where excavation interferes with traffic flow or where work is within the roadway portion of an intersection.
- All excavations must be back-filled or plated at the end of the workday. The City reserves the right to require the permittee to plate open trenches in lieu of back filling.
- Permanent pavement repairs shall be made within 25 calendar days after excavation work is completed. Inspector's approval is required before permanent repairs are made.
- Tree trunks shall be cut to within 4" of curb height. All tree trunks and roots shall be ground to a depth of 18" below grade by a
 mechanical stump grinder to the satisfaction of the Department of Public Works staff. All wood chips shall be removed, hole filled and
 compacted with topsoil.

TRAFFIC CONTROL STANDARD REQUIREMENTS

- Traffic controls throughout permit construction shall conform to the latest edition of the State of California MANUAL ON UNIFORM
 TRAFFIC CONTROL DEVICES (MUTCD) FOR USE IN PERFORMANCE OF WORK UPON HIGHWAYS. Permittee shall provide
 and maintain all such signs, lights, and devices. All barricades in use after sunset must have portable flashers.
- Traffic may be restricted only between the hours of 9:00 a.m. and 3:00 p.m. on all major and secondary highways and subject to review of the Traffic Engineer.
- One lane of traffic in each direction shall be maintained at all times on all major and secondary highways.
- Pedestrian walkways must be maintained with safety fencing or barrier separation for adjacent excavation.
- The cost of any damage to traffic signal control devices shall be the permittee's responsibility and it shall be brought to the immediate attention of the inspector. The Permittee/Contractor shall be responsible for the replacement cost of any inductive loops in the ground (wire sensors for traffic signals) that are in conflict with or damaged by construction.

DUMPSTER REQUIREMENTS – (MUST OBTAIN CONTAINER FROM LIST OF CURRENT APPROVED VENDORS)

- Keep the street clean from debris at all times.
- Do not block/obstruct traffic motorists' line of sight in any direction.
- Dumpster shall not infringe on any driveway approach, Fire Hydrant, Emergency facility, or utility cabinet.
- · Dumpsters must have cones or delineators, reflectors, and reflectorized tape at corners.

CURB AND GUTTER, DRIVEWAY APPROACH, SIDEWALK and CURB CORE REQUIREMENTS

- City's trench standards shall be adhered to.
- Remove any/all markings following construction.
- Remove and Replace curb and gutter at the edge of the asphalt and haul materials to a recycling center. Provide Load Ticket to the Inspector. (Do not cut Asphalt in the street unless directed to do so by the Department of Public Works staff).
- Install monolithic section of curb and gutter.
- Must remove and replace Concrete Score line to Score line or as directed by the City staff.
- Install a minimum of 6-inch thick 3,250-PSI concrete on drivable surfaces and a minimum of 4-inch thick 3,250-PSI concrete in other places.
- Follow American Public Works Association (APWA) standards for Curb Core (Standards available at the City of Rancho Palos Verdes/Department of Public Works).

To schedule an inspection, please visit http://www.rpvca.gov/FormCenter/Public-Works-8/Encroachment-Inspection-ERequest-58 or dial (310) 544-5338. If calling please include the permit number, job address and your contact information. Contact the City of Rancho Palos Verdes Department of Public Works for questions (310) 544-5252 City Hall Hours: Monday – Thursday 7:30 AM – 5:30PM and Fridays 7:30AM – 4:30PM Closed Daily from 12:00PM – 1:00PM. www.rpvca.gov